



CTI-2485-220

FOOD GRADE HIGH-TEMPERATURE ANTI-DRIP CHAIN LUBRICANT

CTI-2485-220 utilizes advanced synthetic base stocks that provide exceptional resistance against smoking and carbon buildup. CTI-2485-220 is extremely resistant to dripping and water washout — even in very moist or humid conditions.

ATTRIBUTES

- Conforms to U.S. Food and Drug Administration (FDA) requirements of lubricants with incidental food contact, 21 CFR 178.3570
- Excellent carbon and varnish control
- Superior rust and corrosion control
- Resists water washout
- Excellent oxidative stability at very high temperatures
- High viscosity index
- Very high flash and auto-ignition points for added safety
- Low volatility and carryover into filters and storage tanks
- Exceptional film strength and anti-wear properties
- Very good coolant properties
- Very long fluid life, allowing for extended oil-drain intervals
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	CTI-2485-220
Viscosity Index	113
Viscosity cSt @40°C	220
Viscosity cSt @100°C	21.0
Flash Point °F	490
Auto-Ignition Point °F	740
Pour Point °F	-23
Four Ball, 40 Kg, 1200 RPM, 75°C 1Hr, SCAR DIA mm	.40
Copper Corrosion, 24 Hr	1a