



CTI-6065-46

FOOD-GRADE AIR COMPRESSOR CLEANER AND LUBRICANT

CTI-6065-46 functions as both a fully formulated food-grade compressor lubricant and a cleaner, providing excellent cleaning properties and outstanding protection. Intended for use in varnished and carboned screw compressors, CTI-6065-46 will typically clean a compressor in approximately 2,000 hours. It is designed to not disrupt normal operations and to minimize filter and separator blockage. CTI-6065-46 meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570).

ATTRIBUTES

- Conforms to U.S. Food and Drug Administration (FDA) requirements of lubricants with incidental food contact, 21 CFR 178.3570
- Food-grade formulation
- Fully formulated cleaner and lubricant
- Protects against wear
- Oxidatively stable
- High flash point
- Low volatility
- Excellent film strength
- Controls carbon and varnish formation
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	CTI-6065-46
Viscosity cSt @ 40°C	45
Viscosity cSt @ 100°C	6.9
Viscosity Index	109
Flash Point °F (°C)	453 (234)
Pour Point °F (°C)	-30 (-34)
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/40/0