



CTI-6162-150

FOOD-GRADE HIGH-TEMPERATURE CHAIN LUBRICANT

CTI-6162-150 is the ideal chain lubricant for baking ovens. It is formulated to avoid smoking and carbon buildup under normal operating conditions and is resistant to dripping and washout. CTI-6162-150 meets H1 requirements for applications with incidental food contact and fully complies with the requirements of 21 CFR 178.3570.

ATTRIBUTES

- Conforms to U.S. Food and Drug Administration (FDA) requirements of lubricants with incidental food contact, 21 CFR 178.3570
- High viscosity index
- Excellent carbon and varnish control
- Very high flash and auto-ignition points for added safety
- Low volatility and carryover into filters and storage tanks
- Very long fluid life, allowing for extended oil drains
- Excellent film strength and anti-wear properties
- Very good coolant properties
- Excellent rust and corrosion control
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	CTI-6162-150
Color	<.5
Flash Point °F	521
Viscosity cSt @ 40°C	145.1
Viscosity cSt @ 100°C	15.9
Pour Point °F	-22
Cu Strip Corrosion	1a

CTI-6162-150 - REVISED 01/2015

The Comlube Technology Inc products provided are approximate equivalents to competitive fluids. It should only be used as a general guide, and not serve as a sole resource for determining the correct lubricant for a particular application. Please consult a Comlube Technology Inc representative to ensure that the replacement fluid is the correct choice for the application.