



---

# CTI-6162-220

## FOOD-GRADE HIGH-TEMPERATURE CHAIN LUBRICANT

---

CTI-6162-220 is the ideal chain lubricant for baking ovens. It is formulated to avoid smoking and carbon buildup under normal operating conditions and is resistant to dripping and washout. CTI-6162-220 meets H1 requirements for applications with incidental food contact and fully complies with the requirements of 21 CFR 178.3570.

### ATTRIBUTES

- Conforms to U.S. Food and Drug Administration (FDA) requirements of lubricants with incidental food contact, 21 CFR 178.3570
- High viscosity index
- Excellent carbon and varnish control
- Very high flash and auto-ignition points for added safety
- Low volatility and carryover into filters and storage tanks
- Very long fluid life, allowing for extended oil drains
- Excellent film strength and anti-wear properties
- Very good coolant properties
- Excellent rust and corrosion control
- Non-toxic/non-hazardous

### TYPICAL PROPERTIES

Lubrication Properties	CTI-6162-220
Color	<.5
Flash Point °F	525
Viscosity cSt @ 40°C	218
Viscosity cSt @ 100°C	20.8
Pour Point °F	-18
Cu Strip Corrosion	1a

#### **CTI-6162-220 - REVISED 01 / 2015**

The Comlube Technology Inc products provided are approximate equivalents to competitive fluids. It should only be used as a general guide, and not serve as a sole resource for determining the correct lubricant for a particular application. Please consult a Comlube Technology Inc representative to ensure that the replacement fluid is the correct choice for the application.