



CTI-6531-220

SYNTHETIC GEAR LUBRICANT

CTI-6531-220 is designed for use in a wide range of gear applications. It is formulated to provide a long oil life with excellent oxidative stability, film strength, lubricity and wear protection. It offers outstanding protection — even in the most demanding applications.

ATTRIBUTES

- Conforms to U.S. Food and Drug Administration (FDA) requirements of lubricants with incidental food contact, 21 CFR 178.3570
- Excellent lubricity
- High film strength
- Long oil life
- Controls carbon and varnish formation
- Superior dispersant properties
- Resists water contamination
- Protects against rust and corrosion
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	CTI-6531-220
Viscosity cSt @ 40°C	220
Viscosity cSt @ 100°C	21.9
Viscosity Index	120
Flash Point °F (°C)	520 (271)
Pour Point °F (°C)	-45 (-43)
Timken OK Load, Kg	40
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/40/0

CTI-6531-220 - REVISED 01 / 2015

The Comlube Technology Inc products provided are approximate equivalents to competitive fluids. It should only be used as a general guide, and not serve as a sole resource for determining the correct lubricant for a particular application. Please consult a Comlube Technology Inc representative to ensure that the replacement fluid is the correct choice for the application.